



<https://www.freeadsz.co.uk/x-249765-z>

conform to PCI Express 2.0 standard.) 2 x PCI slots						Internal I/O Connectors						1 x 24-pin ATX main power connector 1 x 4-pin 12V power connector 4 x SATA 3Gb/s connectors 1 x ATA 3Gb/s connector					
1 x mSATA connector 1 x 6-pin fan header 2 x 5-pin fan header 1 x power fan header 1 x front panel header 1 x front panel audio header 1 x S/PDIF Out header 3 x USB 2.0 headers 1 x FireWire 800 header 1 x eSATA header 1 x IEEE 1394 port header 1 x RJ-45 Ethernet port header 1 x Trivial Transfer Protocol (TPP) header						Back Panel Connectors						1 x PS/2 keyboard/mouse port 1 x HDMI port 1 x optical S/PDIF Out connector 1 x IEEE 1394 ports 2 x USB 2.0/1.1 ports 2 x USB 3.0/2.0 ports 1 x RJ-45 port 6 x audio jacks (center/Subwoofer/Speaker Out/Rear Speaker Out/Side Speaker Out/Line In/Line Out/Microphone)					
I/O Controller						Gigabyte IT8728 chip						Firmware Monitoring System voltage detection CPU/System temperature detection CPU/System Power fan speed detection CPU overheating warning CPU/System/Power fan fail warning CPU/System fan speed control Whether the CPU/system fan speed control function is supported will depend on the CPU/system cooler you install.					
BIOS						2 x 32											



Mbit flash Use of licensed AWARD BIOS Support for DualBIOS™ PnP 1.0a, DMI 2.0, SM BIOS 2.4, ACPI 1.0b Unique Features Support for @BIOS Support for Q-Flash Support for Xpress BIOS Rescue Support for Download Center Support for Xpress Install Support for Xpress Recovery2 Support for EasyTune * Available functions in EasyTune may differ by motherboard model. Support for Dynamic Energy Saver™ 2 Support for Smart 6™ Support for Auto Green Support for eXtreme Hard Drive (X.H.D) Support for ON/OFF Charge Support for Cloud OC Support for 3TB+ Unlock Support for TouchBIOS Support for Q-Share Operating System Support for Microsoft® Windows® 8/7/Vista/XP Form Factor ATX Form Factor; 30.5cm x 24