



The Stringing Gun EZ50 by Zeitler is used to feed a special pull line promptly and efficiently into conduits of Ø 18 to 50 mm (internal diameter) for electrical installation in private construction.

Easy to apply even in buckled conduits, junction boxes, sockets and plugs.

The simple way to blow or suck pull line.

Facts

- Blow or suck pull line without compressor
- For all commercial pipe work (internal diameter from 18 to 50 mm)
- Appropriate for flexible conduits
- Installations in the range of private, office and industrial buildings
- Huge time saving in cable feeding
- Feeding of several hundred meters
- Lightweight and compact
- Excellent accessibility, even in confined spaces
- Easy to handle
- Double function (blowing and suction mode)

- Perfect and strong to solve pull line
- Strong in any car
- The best choice for motor

Zeidler AG
Springing Guns and stable feeding
Sonnhalde CH-6206 Neuenkirch/Switzerland
Tel. +41 (0)41 467 16 14
Fax +41 (0)41 467 20 35
snow contact info



<https://www.freadsz.co.uk/x-523605-z>




<https://www.freadsz.co.uk/x-523605-z>



<https://www.freedasz.co.uk/x-523605-z>



<https://www.freadsz.co.uk/x-523605-z>



05-Z
S
S
C
T
F
S



06-z
kirchy
37 16
37 20



<https://www.treedadsz.co.uk/x-5236>
06-Z



<https://www.11eeadsz.co.uk/X-3236>
05-Z



05-Z
<https://www.ice.dauz.co.uk/n/a-220>



<https://www.iteadusz.co.uk/A-3230>
05-z

Stringing Gun EZ50

for all electrical installations

Intended Use:

- insert a special pull line in all commercial conduits (int. ø 18 to 50 mm)
- installations in the range of private houses, office and industrial buildings
- for all commercial boxes, junction boxes, sockets, lamp boxes etc. (even in very confined spaces)
- problems with f.e. kinked conduits can be solved by switching to suction mode, sucking the pull line from opposite end

Function:

- apply line brake
- fit joint/nozzle appropriate to internal conduit diameter
- firstly blow through the conduit with air, check if penetrable tube/correct tube
- make either a loop or fix a bead to the pull line
- release line brake
- blow pull line in without interrupting, observe uncoiling in cylinder
- release switch and close nozzle with a finger
- apply line brake and cut off pull line
- fix wire/s to the pull line and start pulling

Stringing Gun EZ50

Standard equipment in strong plastic case

- 1 Stringing Gun EZ50
- 2 pull line rolls ø 1 mm, approx. 900 m, tensile strength approx. 24 kg
- 1 suction device
- Components set A: 2 joints ½", reduction 19/12 mm and nozzle int. ø 9,5 mm
- Components set B: 3 joints ¾", nozzle int. ø 16 mm plus nozzle int. ø 19 mm
- 1 special nozzle black, for internal diameter from 25 to 50 mm
- 1 special nozzle with 90° angle, external diameter 12 mm (only in connection with special nozzle black)
- 3 beads of ø 11, 13 and 16 mm each
- Operating